IN THE CLAIMS

Claims 1-10 (Cancelled).

11. (Previously Presented) A method, comprising:

assigning a private network-network interface (PNNI) peer group identification to a device to be coupled with an asynchronous transfer mode (ATM) network based on a manufacturer of the device and a product group to which the device belongs; and

auto-configuring the device at a point of manufacture with an ATM address using the assigned PNNI peer group identification.

- 12. (Previously Presented) The method of claim 11, wherein the PNNI peer group identification includes a two bit field indicating manufacturer.
- 13. (Previously Presented) The method of claim 11, wherein the PNNI peer group identification includes a four bit field indicating product group.
- 14. (Previously Presented) The method of claim 11, wherein the ATM address includes a switch identification field identifying a switch to which the device will be connected or a default switch.
- 15. (Previously Presented) The method of claim 14, wherein the switch identification field can be altered at a point of installation.
- 16. (Previously Presented) The method of claim 14, wherein the switch identification field consists of a media access control (MAC) address.
- 17. (Previously Presented) The method of claim 14, wherein the switch identification

 Application No.: 09/852,755

 -3- Attorney Docket No.: 81862P232D

field consists of six bytes.

- 18. (Previously Presented) The method of claim 11, wherein the ATM address includes a device identification field unique to the device.
- 19. (Previously Presented) The method of claim 18, wherein the device identification field can be altered at a point of installation.
- 20. (Previously Presented) The method of claim 18, wherein the device identification field consists of a media access control (MAC) address.
- 21. (Previously Presented) The method of claim 18, wherein the device identification field consists of six bytes.
- 22. (Previously Presented) A machine-readable storage medium tangibly embodying a sequence of instructions executable by a machine to perform a method comprising:

assigning a private network-network interface (PNNI) peer group identification to a device to be coupled with an asynchronous transfer mode (ATM) network based on a manufacturer of the device and a product group to which the device belongs; and auto-configuring the device at a point of manufacture with an ATM address using the assigned PNNI peer group identification.

- 23. (Previously Presented) The machine-readable storage medium of claim 22, wherein the PNNI peer group identification includes a two bit field indicating manufacturer.
- 24. (Previously Presented) The machine-readable storage medium of claim 22, wherein the PNNI peer group identification includes a four bit field indicating product

 Application No.: 09/852,755

 4- Attorney Docket No.: 81862P232D

group.

- 25. (Previously Presented) The machine-readable storage medium of claim 22, wherein the ATM address includes a switch identification field identifying a switch to which the device will be connected or a default switch.
- 26. (Previously Presented) The machine-readable storage medium of claim 25, wherein the switch identification field can be altered at a point of installation.
- 27. (Previously Presented) The machine-readable storage medium of claim 25, wherein the switch identification field consists of a media access control (MAC) address.
- 28. (Previously Presented) The machine-readable storage medium of claim 25, wherein the switch identification field consists of six bytes.
- 29. (Previously Presented) The machine-readable storage medium of claim 22, wherein the ATM address includes a device identification field unique to the device.
- 30. (Previously Presented) The machine-readable storage medium of claim 29, wherein the device identification field can be altered at a point of installation.
- 31. (Previously Presented) The machine-readable storage medium of claim 29, wherein the device identification field consists of a media access control (MAC) address.
- 32. (Previously Presented) The machine-readable storage medium of claim 29, wherein the device identification field consists of six bytes.

Claims 33-43 (Canceled)